

FEEL THE HEAT!

DragonFire SoftTop 2 & 4 Seats UTV Black

Congratulations on your purchase of the DragonFire SoftTop. This product has been designed around the stock cage to give you a lightweight, easy to use, and stylish roof on your factory UTV. Be sure to check out the full line of DragonFire Accessories for your vehicle at your local authorized dealer or online at <http://www.DragonFireRacing.com>

2 Seats UTV SoftTop: 6 Clamps
4 Seats UTV SoftTop: 8 Clamps

! WARNING

- Read and understand these instructions before installing product
- This product does not provide roll over protection
- Ensure doors are securely latched and locked prior to operating vehicle
- Discoloration may occur overtime due to environment condition
- Do not use product if there are any signs of damage

Disclaimer

Off road activities can be hazardous and could lead to injury, dismemberment, paralysis and death. No warranty of representation is made as to the products ability to protect the user from any injury or death. The user assumes that risk. The acceptance and /or use of this merchandise purchased from DragonFire by the customer hereby shall release DragonFire from any and all liability pertaining to the use of such merchandise.

Tools Required
5/16" Socket
Ratchet
Flat Screw Driver

Step 1: Place vehicle on a flat and level surface. Place gear selector in "Park" and remove keys from the ignition.

Step 2: Lay the SoftTop out on the floor upside down (should be able to see Velcro mounts) insert rubberized band clamps through sleeve located in corners of the SoftTop. Make sure the bolt head side of band clamp is on top of elastic portion of band clamp cover (Figure A & B).

Step 3: Place SoftTop on the top of vehicle cage with the Velcro mounts pointed down. The wider side portion of SoftTop is the back (Figure C).



A



B



C

Step 4: Start by wrapping Velcro mounts around the cage at the point they fall in; Make sure the straps are securely fastened. Do not worry about alignment at this time; work from front to back of cage (Figure D).

Step 5: Loosely install corner band clamp mounts using 5/16" socket or flat screwdriver. The clamps at the rear of the cage must go through corner gussets of the cage (Figure E).

Note: 4 seat application has no corner gussets

Step 6: Once all band clamps have been installed pull each band clamp mount taught and tighten band clamps. This process may need to be repeated if proper alignment is not reached at the time of completion (Figure F).



Step 7: Cover band clamps with stretchy Velcro cover at each corner (Figure G).

Step 8: This completes installation. Time to ride and enjoy!

ProTip: Periodically check all hardware and re-tighten if needed.

For further assistance please contact us at
customerservice@dragonfireracing.com or 1-800-708-9803.

